

# S18 UC

UNDERCOUNTER VERSION



Expect more with this high-capacity solution that delivers **premium chilled**, **sparkling**, **and ambient** water on demand.

This advanced system produces up to 180 liters per hour\* of premium chilled, sparkling, and ambient water, perfect for high volume applications including hotels and restaurants.

Featuring an 11" dispense height, rapid cold carbonation, and manual faucets for dependable dispensing, the S18 UC makes quick, efficient bottle-filling an easy task for any user.

## **System Highlights:**

- 3-tap chrome dispensing tower features chilled, sparkling, and ambient water
- 4-Stage advanced filtration system can be easily mounted to chiller or installed remotely
- Carbonating chiller and purification system installs remotely or under counter
- Insulated trunkline and water recirculation to ensure optimal temperature from chiller to tap



The S18 UC sets itself apart as a high-end, space-saving system delivering generous capacity and exceptional still and sparkling water.

### **Features:**

- Unrivaled 22lb ice bank chills a higher volume of cold water
- Utilizes R290 environmentally friendly natural refrigerant
- Equipped with a 1.7 liter sparkling tank
- · Programmable flow meter tracks usage and allows more consistent scheduled service and filter changes
- · Heavy duty rotary faucets allow for pressure and flow control to limit splashing
- Easily connects to external CO2\*\*
- Removable drip tray\*\*\*

### **3-Tap Chrome Tower**



#### **Undercounter Chiller**



25.2"

Tap Dimensions	25.5"h x 5.2"w x 22.3"d
Drip tray dimensions	1.3"h x 15.0"w x 5.0"d
Undercounter dimensions	25.2"h x 18.0"w x 23"d – Width includes 4.3" for filtration housing
Ventilation clearance requirement	See detailed installation guide for more information
Dispense height	11.0"h
Tap dry weight	20 lbs
Undercounter dry weight	94 lbs
Tower tap hole size requirement	2.0"
Chilling capacity	180 liters per hour*
Cooling technology	Ice bath chilling technology
Recommended water pressure	50 psi

Available external CO2 tank or bulk CO2 supply connection; Operates at 55 PSI



Rated voltage/frequency / running amps

Ice block weight

CO2 specificatio

Model number

\*Capacity dependent on source water temperature

22 lbs

S18 UC

115 V / 60 Hz / 7 amps

<sup>\*\*</sup>CO<sub>2</sub> regulator included

<sup>\*\*\*</sup>Optional recessed drip tray