

# WL50

High-performance water dispenser

The WL50 is equipped with premium filtration and an integrated in-tank LED UV, making it ideal for high-traffic environments.

# Advanced technology:



## **High-Performance Filtration**

Configured with 5-stage reverse osmosis filtration or 4-stage micro-filtration.



#### In-tank LED UV

In-tank LED UV technology helps maintain system cleanliness.



## Surface protection technology\*

Key surfaces are infused with surface protection technology, inhibiting the growth of odor and stain-causing microbes.



#### Large capacity hot tank

Equipped with 1.1 gallon stainless steel hot tank.



## Number of users: 50+

\*Surface protection technology protects surfaces from odor and stain-causing microbes. It does not protect users against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

## **Features**

Reverse osmosis with mineral add back or 4-stage micro-filtration

Quick-change filtration system allows for easier filter changes and fewer fittings

Gravity-fed stainless steel storage tank

Patented recirculating cold water system pumps water by the in-tank LED UV light every 15 minutes to re-chill and maintain fresh, great tasting water

Fast cold water dispense rate is double the rate of a traditional cooler

Equipped with internal air filter to minimize introduction of

Float-style leak detection system provides peace of mind and reduces the risk of leaks

Illuminated display and dispense area turns blue when dispensing cold water and turns red when dispensing hot for a better user experience

# Temperature options

cold

hot





# Technical specifications

#### **Dimensions**

11.8" (W) x 50.3" (H) x 17.2" (D)

#### Dispense area height

#### Weight

59 lbs

#### Filtration options

Reverse osmosis or 4-stage micro-filtration

#### Storage capacity

Cold tank: ~ 2.2 gal Hot tank: ~ 1.1 gal

## Rated Voltage / Frequency

110V/60Hz

#### Water temperatures settings

Adjustable Cold Settings: 37°F/41°F/44°F Default Hot Setting: 185° F

#### Dispensing method

Capacitive touch sensor

# Purification process\*





residue.



Pre-carbon Filter Reduces chlorine and chemicals.



**Reverse Osmosis** Membrane Reduces dissolved solids, pharmaceuticals, and

metals.



Mineral Add-Back Filter





# Post-carbon Filter

Final polishing filter ensures great taste.

> \*Also available in 4-stage Micro-Filtration: Sediment Filter, Pre-Carbon Filter, Lead/Cyst CBC Filter, and Post-Carbon Filter.

## Contact us today

Premium Pure Water 311 Route 46 West Unit B Fairfield, NJ 07004 973-259-6138 sales@premium-purewater.com

## Tested and certified





The Waterlogic WL50 is certified by IAPMO R&T against NSF/ANSI/CAN 61: Q≤1, NSF/ANSI-372, and CSA B483.1 for the specific performance claims as verified and substantiated by test data. The Waterlogic WL50 is also certified to NSF/ANSI-53 for the reduction of lead and cysts and NSF/ANSI-42 for the reduction of Chlorine and Taste & Odor when using the Waterlogic WLLR-12 filter.